

Intermittently Associated Mobile Cognitive Radio Networks Using Portability Assisted Routing

Dr.B. Karthik, G. Meena Kumari, Dr.M. Jasmin, Dr.S. Arulselvi

Received: 04 Jan 2018 ▪ Revised: 09 March 2018 ▪ Accepted: 02 April 2018

Abstract: In versatile specially appointed intellectual radio systems, with accessible range groups for optional clients may or may not exist incidentally, because of the dynamism of the essential client exercises. Customary CRN steering calculations, which normally overlook the discontinuous availability of system topology, and customary portability helped directing calculations, which for the most part disregard the range accessibility, are clearly unacceptable. To handle this test, a Assisted Mobility Routing calculation with Spectrum Awareness (MARSA) is proposed to choose transfers in light of not just the likelihood that a hub meets the goal additionally the possibility that exists no less than one accessible channel. This dissertation is proposed to bring the possibility of versatility helped steering to manage the irregularly associated characteristic of versatile impromptu CRNs, and the first to improve the portability helped directing by considering the worldly, spatial, and range spaces in the meantime. Our reenactment comes about show the predominance of MARSA over customary calculations in discontinuously associated portable CRNs.

Keywords: CRN, ICMCRN, MARSA, Portability Assisted Routing.

INTRODUCTION AND MOTIVATION

These days, psychological radio systems administration (CRN) has gotten a considerable measure of consideration since it bears the guarantee of lightening the range shortage issue. This paper, consist of a mobile impromptu CRN, when two hubs can trade their information as it were when they enter each other's transmission path and there exists no less than one accessible channel between them. This is named an Intermittently Connected Mobile CRN (ICMCRN), that ordinarily don't have incidentally table ways among accessible range. In ICMCRNs, conventional CRN steering conventions are definitely not proper in light of the fact that they normally expect so as to accessible time exercises over essential groups time expected to experience a round of interchanges. Notwithstanding, this presumption does not generally remain constant particularly when the essential clients' usage of the authorized spectrum is high.

Truth be told, if the sit without moving and occupied lengths of the authorized range are exchanged often inside a brief span, the range is difficult to utilize despite the fact that the usage is low. This is since before utilizing the authorized range for information correspondences, auxiliary clients must intellect the channel and check with with others for conceivable range distribution. In this way if the season of these procedures is equivalent to the sit without moving term, the range may change to be inaccessible rapidly from the sit still state, to a great extent restricting the sum of information to be traded.

Dr.B. Karthik, Associate Professor, Department of Electronics and Communication Engineering, BIST, BIHER, Bharath Institute of Higher Education & Research, Selaiyur, Chennai. E-mail: karthik.ece@bharathuniv.ac.in

G. Meena Kumari, Associate Professor, Department of Electronics and Communication Engineering, BIST, BIHER, Bharath Institute of Higher Education & Research, Selaiyur, Chennai. E-mail: meensg85@gmail.com

Dr.M. Jasmin, Associate Professor, Department of Electronics and Communication Engineering, BIST, BIHER, Bharath Institute of Higher Education & Research, Selaiyur, Chennai.

Dr.S. Arulselvi, Associate Professor, Department of Electronics and Communication Engineering, BIST, BIHER, Bharath Institute of Higher Education & Research, Selaiyur, Chennai.

Because of the way of irregular network in ICMCRNs, a characteristic approach to manage the steering issue is to receive the versatility helped directing strategy, i.e., store carry- forward. In any case, straight forwardly applying the conventional versatility helped steering components for ICMCRNs may prompt wasteful steering execution due to the disgraceful basis for selecting transfers. A decent transfer in customary portability helped steering that lone considers the opportunity to get in touch with the goal may not be a decent in ICMCRNs on the grounds that if range band does not exists amid their contact, the contact gets to be worthless. Indisputably, for ICMCRNs, none of the customary CRN steering calculations are fitting because of the supposition of the presence of stable end-to-end ways nor the conventional versatility helped steering calculations are appropriate since they just consider worldly and spatial spaces while the steering productivity of ICMCRNs too relies on upon the range space.

To deal with the steering test of ICMCRNs, a Mobility-Assisted Directing calculation with Spectrum Awareness (MARSA) is proposed in this paper, which chooses transfers by considering not just the chance that a hub meets the goal additionally the chance at which there exists no less than one accessible channel when they meet. At the end of the day, MARSA considers the data from the transient, spatial, and range areas for directing way development. To the best of our insight, this paper is the first to present the possibility of portability helped steering to ICMCRNs to manage the irregularly associated property, and the in the first place to upgrade the versatility helped steering with range attention to adjust the directing test.

DESIGN MOTIVATION

In this segment, we exhibit the portability attributes of the hubs also, the range abused by MARSA, which are acquired by breaking down this present reality marvel and follow information.

NODE MOBILITY

In true, the versatility of hubs, (for example, people alternately vehicles) is generally exceptionally energetic. Busses what's more, planes touch base in specific spots at specific times under typical conditions.

Consequently, the versatility of hubs displays spatial and fleeting normality. This quality is confirmed by the information got through following the directions of 100,000 unknown cell phone clients for a 6 months time frame, in which the hubs are found in their initial two favored spots with a likelihood more than 40 %. A 3 months record catching the versatility examples of 50,000 hubs picked from around 10 million unknown cell phone clients likewise exhibits that individuals more often than not stay in their exceptionally went by spots at a hourly consistency.

Spectrum Mobility Shows Regularity

Numerous certifiable datasets show that the exercises of PUs are not irregular. For instance, the dataset] in view of the charging data of one European cell phone administrator shows the change of patterns of normal number of calls per hour and the normal call for every weekday in a week are fundamentally the same as. The roughly normal practices leads to the inexact consistency of the portability of the range that can be accessed for SUs. The portability normality of the hubs mixes us to plan an ICMCRN directing system also, a hand-off choice calculation, which will be displayed in the following two segments.

THE FRAMEWORK FOR MARSA

In light of the perceptions from this present reality information, the regularities of the hubs and the range are firmly identified with the spots individuals visit.

Definition 4.1 (Home). *The home of a hub j , signified by H_j , is an arrangement of zones it typically visits*

There are two straightforward procedures for deciding the home of a hub: 1) a hub can arrange the zones it typically reaches as if it is its home; and/or 2) it can powerfully include a zone to its home once the meeting recurrence of the zone is bigger than a given limit. Correspondingly, either statically or powerfully a zone can be erased from a hub's home.

Neighbor Set: The neighbor set of hub j , indicated by N_j , is an arrangement of hubs so as to can convey straightforwardly with j if there exists no less than one accessible channel.

Any two hubs situated at similar zone can discuss specifically with each other if no less than one channel is accessible. In view of this presumption, every one of the hubs secured by the zone where j lives

have a place with N_j . More by and large, N_j incorporates the hubs in a neighboring zone that can speak with j straightforwardly if range is accessible.

Destination Zone: The zone the goal d as of now dwells is the goal zone, indicated by Z_d .

Spectrum Availability: The range accessibility is the likelihood that there exists more than an accessible channel to convey.

In MARSA, the ideal opportunity for every zone is partitioned into equivalent length cycles. Inside every cycle, it is additionally partitioned into rise to length interims. An interim's length relies on upon the variety of the accessible range: if it is huge, it ought to be lessened; else, it ought to be extended. Because of the day by day standard practices of individuals, a hub should occasionally show up in its home zones at settled interval(s) amid every cycle.

Highly Available Visit: A exceptionally available visit is the range accessibility is greaterr than a given limit T_h .

Two hubs trade their directing data at whatever point they contact is required. The data conveyed by every hub i is spoken to as three-tuples $fZ_j; T_i j; P_i j g$, with one for every home zone, where $Z_j \in H_i$, $T_i j \in [f_{t_i j 1}; t_{i j 2}; \dots g]$ is the arrangement of beginning time at which i generally visits Z_j , and $P_i j \in [f_{p_i j 1}; p_{i j 2}; \dots g]$, with every $p_{i j k}$ speaking to the range accessibility in the meeting interim beginning from $t_{i j k}$.




Figure: Node appears home zones each cycle

Since the range portability is standard in all actuality the range accessibility in every zone of every interim can be derived by investigating the long haul measurable information. It is necessities to think the distribution of the range amongst various SUs: the many of the SUs viewing for the same channel, the lower the range accessibility. Thus the strategy for sending the halfway looked after database to get accessible channel data is broadly utilized as a part of CRNs.

DESCRIPTION OF MARSA

This area points of interest the MARSA calculation. Its code is given in Algorithm. Since every hub has capacity, any hub j at present holding the information detects the range occasionally, as proposed by In the event that no less than other channel is accessible, hub j needs to upgrade its neighbor set N_j .

Algorithm 1 Pseudocode of MARSA

```

1: repeat
2:   if at least one channel is available then
3:     Update  $N_j$  if needed;  $\triangleright$  Node  $j$  may be the source
       or a relay.
4:     if  $d \in N_j$  then  $\triangleright d$  is the destination;
5:       send( $B, d$ ); return
6:     end if
7:     for each node  $i \in N_j$  do
8:       exchange routing information with  $i$ ;
9:       if  $O(i, j) = \text{True} \wedge$  for  $\forall k \in N_j \setminus \{i\}, O(i, k) = \text{True}$ 
       then  $\triangleright$  If  $i$  is better than  $j$  and  $j$ 's neighborhood;
10:        send( $B, i$ );
11:      end if
12:    end for
13:  end if
14: until the data expires;

```

Algorithm 2 Function $O\delta i; jP$

```

 $A_i \leftarrow \{m \mid 0 \leq t_{dm}^i - t_c \leq t_l\}; A_j \leftarrow \{n \mid 0 \leq t_{dn}^j - t_c \leq t_l\}$ 
▷ Compute the set of visits whose starting time is before
the lifetime of the data;
 $B_i \leftarrow \{m \mid p_{dm}^i > T_h, m \in A_i\}; B_j \leftarrow \{n \mid p_{dn}^j > T_h, n \in A_j\}$ 
▷ Compute the set of highly available visits.
if  $B_i \neq \emptyset \wedge B_j \neq \emptyset$  then
  if  $\min\{t_{dm}^i \mid m \in B_i\} < \min\{t_{dn}^j \mid n \in B_j\}$  then
    return True
  else
    return False
  end if
end if
): if  $B_i \neq \emptyset \wedge B_j = \emptyset$  then
  : return True
  ): end if
) if  $B_i = \emptyset \wedge B_j \neq \emptyset$  then
  : return False
  ) end if
) if  $B_i = \emptyset \wedge B_j = \emptyset$  then
  ? if  $A_i = \emptyset$  then
  : return False
  ) else ▷  $A_i \neq \emptyset$ .
  ) if  $A_j = \emptyset \vee (A_j \neq \emptyset \wedge \min\{t_{dm}^i \mid m \in A_i\} <$ 
   $\min\{t_{dn}^j \mid n \in A_j\})$  then
  : return True
  ) else
  : return False
  ) end if
) end if
): end if

```

The capacity judges if hub i is further ideal than j to go about as a transfer. In the event that it is yes, then it returns True; or generally False. Thus the procedure of Function is given in the above Algorithm, where t_c is the present time where $astl$ is the rest of the lifetime of the information. For 2 hubs in which both having no less than one profoundly accessible reaches to Z_d , or both just having no less than one stay as opposed to the exceedingly accessible one to Z_d , if the most punctual visit of one hub is earlier than the other, which is more ideal.

NUMERICAL VALIDATION

To approve the hypothetical examination, we build a recreated organize which contains 10 zones. Every zone at every interim may have expresses: a sit out of gear state what's more, a bustling state. We arbitrarily appoint the sit still and occupied various at various intervals. Worldly and land varieties the allotted spectrum range from 15 % to 85 %. Thus we set the range accessibility to be an irregular number running from 15 % to 30 % for the bustling state. If an information could be conveyed effectively in a zone amid an interim relies on upon the range accessibility at that zone amid that interim. $Th = 0.5$ in this reproduction.




Figure: Validating the average delivery latency

There are 200 mobile hubs and 100 stationary hubs. Every versatile hub moves in light of the time-variation group portability (TVCM) display, where every hub is haphazardly dispensed some home zones as its group and 24 interim periods, to be specific 24 hours. On the off chance that a hub should interim, it has a bigger likelihood to visit the coveted zone. Anode moves as indicated by the arbitrary bearing portability demonstrate inside a zone. We select every single portable hub stationary hubs as goals living at the first, fourth, seventh, and tenth lines and sections of the 10 framework organize. We test the conveyance proportion, conveyance inertness of every correspondence combine. Every analysis is rehased 50 times various arbitrary seeds for factual certainty. The normal rate at which every hub contacts with others is set by factual estimations of the recreation. In our hypothetical examination, for every goal, we decide the sort of the hubs toward the start of the entire reproduction to get and that toward the start of every interim to get the state move network, lastly to compute the normal conveyance proportion and latency.1

PERFORMANCE ANALYSIS

Here, the execution of MARSA IS accessed. For this reason we build up a remain solitary, occasion test system utilizing both this present reality information and the engineered information as the sources of info. Thus in this paper, we just look at our steering plan with its rearranged renditions and a few customary portability helped directing calculations, which are all presented in the accompanying:

The Epidemic Algorithm

In the plague calculation, a hub duplicates the information to each recently experienced hub that does the information s an accessible channel.

The Basic Algorithm

In the essential calculation, finds a neighboring hub ideal as well as its different neighbors, it exchanges the information to that neighbor. At that point the information won't be conveyed to whatever other hub with the exception of the goal. At the end of the day, the fundamental calculation is a solitary duplicate single-hand-off rendition of MARSA.




Figure: Delivery latency comparison




Figure: Impact of T_h on the number of relays

CONCLUSION

This presentation brings the possibility of assisted mobility directing to portable impromptu CRNs. The future directing calculation called MARSA will not consider the possibility that a hub meets the goal, yet additionally the possibility of fruitful interchanges when two hubs meet. Thus a point by point examination on MARSA and utilize reenactment study to approve our examination is made. The execution of MARSA is additionally assessed in light of both genuine follow information and engineered information. By contrasting with best in class portability based calculations, we watch that MARSA obviously performs well as far as conveyance dormancy and conveyance proportion. In our future research, we will mutually consider transfer determination and range administration (range detecting, sharing, and versatility) for ICMCRNs as impedance affects the viability of transfer choice.

REFERENCES

- [1] Das, J., Das, M. P., & Velusamy, P. (2013). Sesbania grandiflora leaf extract mediated green synthesis of antibacterial silver nanoparticles against selected human pathogens. *Spectrochimica Acta Part A: Molecular and Biomolecular Spectroscopy*, 104, 265-270.
- [2] Umanath, K.P.S.S.K., Palanikumar, K., & Selvamani, S. T. (2013). Analysis of dry sliding wear behaviour of Al6061/SiC/Al2O3 hybrid metal matrix composites. *Composites Part B: Engineering*, 53, 159-168.
- [3] Udayakumar, R., Khanaa, V., Saravanan, T., & Saritha, G. (1786). Cross layer optimization for wireless network (WIMAX). *Middle-East Journal of Scientific Research*, 16(12), 1786-1789.
- [4] Kumaravel, A., & Rangarajan, K. (2013). Algorithm for automaton specification for exploring dynamic labyrinths. *Indian Journal of Science and Technology*, 6(5S), 4554-4559.
- [5] Pieger, S., Salman, A., & Bidra, A.S. (2014). Clinical outcomes of lithium disilicate single crowns and partial fixed dental prostheses: a systematic review. *The Journal of prosthetic dentistry*, 112(1), 22-30.
- [6] Vijayaraghavan, K., Nalini, S.K., Prakash, N.U., & Madhankumar, D. (2012). One step green synthesis of silver nano/microparticles using extracts of Trachyspermum ammi and Papaver somniferum. *Colloids and Surfaces B: Biointerfaces*, 94, 114-117.
- [7] Khanaa, V., Mohanta, K., & Satheesh, B. (2013). Comparative study of uwb communications over fiber using direct and external modulations. *Indian Journal of Science and Technology*, 6(6), 4845-4847.
- [8] Khanaa, V., Thooyamani, K. P., & Udayakumar, R. (1798). Cognitive radio based network for ISM band real time embedded system. *Middle-East Journal of Scientific Research*, 16(12), 1798-1800.
- [9] Vijayaraghavan, K., Nalini, S.K., Prakash, N.U., & Madhankumar, D. (2012). Biomimetic synthesis of silver nanoparticles by aqueous extract of Syzygium aromaticum. *Materials Letters*, 75, 33-35
- [10] Caroline, M.L., Sankar, R., Indirani, R.M., & Vasudevan, S. (2009). Growth, optical, thermal and dielectric studies of an amino acid organic nonlinear optical material: l-Alanine. *Materials Chemistry and Physics*, 114(1), 490-494.
- [11] Kumaravel, A., & Pradeepa, R. (2013). Efficient molecule reduction for drug design by intelligent search methods. *International Journal of Pharma and Bio Sciences*, 4(2), B1023-B1029.
- [12] Kaviyarasu, K., Manikandan, E., Kennedy, J., Jayachandran, M., Ladchumananandasivam, R., De Gomes, U. U., & Maaza, M. (2016). Synthesis and characterization studies of NiO nanorods for enhancing solar cell efficiency using photon upconversion materials. *Ceramics International*, 42(7), 8385-8394.
- [13] Sengottuvel, P., Satishkumar, S., & Dinakaran, D. (2013). Optimization of multiple characteristics of EDM parameters based on desirability approach and fuzzy modeling. *Procedia Engineering*, 64, 1069-1078.
- [14] Anbuselvi S., Chellaram, C., Jonesh S., Jayanthi L., & Edward J.K.P. (2009). Bioactive potential of coral associated gastropod, Trochus tentorium of Gulf of Mannar, Southeastern India. *J. Med. Sci*, 9(5), 240-244.
- [15] Kaviyarasu, K., Ayeshamariam, A., Manikandan, E., Kennedy, J., Ladchumananandasivam, R., Gomes, U. U., & Maaza, M. (2016). Solution processing of CuSe quantum dots: Photocatalytic activity under RhB for UV and visible-light solar irradiation. *Materials Science and Engineering: B*, 210, 1-9.

- [16] Kumaravel, A., & Udayakumar, R. (2013). Web portal visits patterns predicted by intuitionistic fuzzy approach. *Indian Journal of Science and Technology*, 6(5S), 4549-4553.
- [17] Srinivasan, V., & Saravanan, T. (2013). Reformation and market design of power sector. *Middle-East Journal of Scientific Research*, 16(12), 1763-1767.
- [18] Kaviyarasu, K., Manikandan, E., Kennedy, J., & Maaza, M. (2015). A comparative study on the morphological features of highly ordered MgO: AgO nanocube arrays prepared via a hydrothermal method. *RSC Advances*, 5(100), 82421-82428.
- [19] Kumaravel, A., & Udhayakumarapandian, D. (2013). Construction of meta classifiers for apple scab infections. *International Journal of Pharma and Bio Sciences*, 4(4), B1207-B1213.
- [20] Sankari, S. L., Masthan, K. M. K., Babu, N. A., Bhattacharjee, T., & Elumalai, M. (2012). Apoptosis in cancer-an update. *Asian Pacific journal of cancer prevention*, 13(10), 4873-4878
- [21] Harish, B. N., & Menezes, G. A. (2011). Antimicrobial resistance in typhoidal salmonellae. *Indian journal of medical microbiology*, 29(3), 223-229.
- [22] Manikandan, A., Manikandan, E., Meenatchi, B., Vadivel, S., Jaganathan, S. K., Ladchumananandasivam, R., & Aanand, J. S. (2017). Rare earth element (REE) lanthanum doped zinc oxide (La: ZnO) nanomaterials: synthesis structural optical and antibacterial studies. *Journal of Alloys and Compounds*, 723, 1155-1161.
- [23] Caroline, M. L., & Vasudevan, S. (2008). Growth and characterization of an organic nonlinear optical material: L-alanine alaninium nitrate. *Materials Letters*, 62(15), 2245-2248.
- [24] Saravanan T., Srinivasan V., Udayakumar R. (2013). A approach for visualization of atherosclerosis in coronary artery, Middle - East Journal of Scientific Research, 18(12), 1713-1717.
- [25] Poongothai, S., Ilavarasan, R., & Karrunakaran, C.M. (2010). Simultaneous and accurate determination of vitamins B1, B6, B12 and alpha-lipoic acid in multivitamin capsule by reverse-phase high performance liquid chromatographic method. *International Journal of Pharmacy and Pharmaceutical Sciences*, 2(4), 133-139.
- [26] Udayakumar, R., Khanaa, V., & Saravanan, T. (2013). Synthesis and structural characterization of thin films of SnO₂ prepared by spray pyrolysis technique. *Indian Journal of Science and Technology*, 6(6), 4754-4757
- [27] Anbazhagan, R., Satheesh, B., & Gopalakrishnan, K. (2013). Mathematical modeling and simulation of modern cars in the role of stability analysis. *Indian Journal of Science and Technology*, 6(5S), 4633-4641.
- [28] Caroline, M.L., & Vasudevan, S. (2009). Growth and characterization of bis thiourea cadmium iodide: A semiorganic single crystal. *Materials Chemistry and Physics*, 113(2-3), 670-674.
- [29] Sharmila, S., Jeyanthi Rebecca, L., & Das, M. P. (2012). Production of Biodiesel from *Chaetomorpha antennina* and *Gracilaria corticata*. *Journal of Chemical and Pharmaceutical Research*, 4(11), 4870-4874.
- [30] Kavitha, N.S., & Dr.Singaravel, G. (2018). Survey on Data Aggregation through Orthogonal Set Method for Wireless Sensor Network. *Bonfring International Journal of Networking Technologies and Applications*, 5(2), 12-14.
- [31] Dr.Balasubramaniam, P.M., Michael Jayaraj, J., Mounick Raj, T., Venkatesh, G., & Vasanth Raj, S. (2019). Automated Switching Solar Power Grid Tie Inverter Using Embedded System. *Bonfring International Journal of Power Systems and Integrated Circuits*, 9(1), 5-9.
- [32] Vengatachalam, P., & Vijayakumar (2015). Rain Streaks Detection and Removal from Color-Image Video Using Sparse Representation. *International Scientific Journal on Science Engineering & Technology*, 18(6), 175-180.
- [33] Prathibha, T., & Dr. Mohankumar Naik, B. (2015). High Performance Input Output Block Implementation on FPPFA-An Overview. *International Scientific Journal on Science Engineering & Technology*, 18(6), 211-214.
- [34] Kaur, R., & Patterh, M.S. (2015). Adaptive Digital Predistorter based on Particle Swarm Optimization Algorithm. *International Scientific Journal on Science Engineering & Technology*, 18(8), 272-278.
- [35] Mehdi, F., Farzeen, S., & Jain, S.S. (2015). Healing Phobias using Augmented Reality. *International Scientific Journal on Science Engineering & Technology*, 18(8), 292-296.

- [36] Vijayalakshmi, K., Divya, R., Jayashree, V., Dharani, R., & Dhanalakshmi, B. (2017). Alert System for Fisherman Crossing Border using Lab View. *The SIJ Transactions on Computer Science Engineering & its Applications*, 5(2), 4-7.
- [37] Bharathi Vikkiran, P., Poovarasam, M., Prathap, B., Praveen Raj, S., & Rangarajan, E. (2017). Advances in Image Processing for Detection of Plant Disease. *The SIJ Transactions on Computer Science Engineering & its Applications*, 5(2), 8-10.
- [38] Saravana Kumar, R., Kavipriya, G., Mahalakshmi, R., Nandhini, K., & Nishanthi, V. (2017). Evergreen based Agriculture Irrigation System using IoT. *The SIJ Transactions on Computer Science Engineering & its Applications*, 5(2), 11-14.
- [39] Nandhini, M., & Dr.Madhavi, S. (2019). Provisioning of Data Security for File Transformation on Multi Cloud Storage. *Bonfring International Journal of Software Engineering and Soft Computing*, 9(1), 15-16.
- [40] Thooyamani, K.P., Khanaa, V., & Udayakumar, R. (2013). An integrated agent system for e-mail coordination using jade. *Indian Journal of Science and Technology*, 6(6), 4758-4761.
- [41] Caroline, M. L., Kandasamy, A., Mohan, R., & Vasudevan, S. (2009). Growth and characterization of dichlorobis L-proline Zn (II): A semiorganic nonlinear optical single crystal. *Journal of Crystal Growth*, 311(4), 1161-1165.
- [42] Caroline, M.L., & Vasudevan, S. (2009). Growth and characterization of L-phenylalanine nitric acid, a new organic nonlinear optical material. *Materials Letters*, 63(1), 41-44.
- [43] Kaviyarasu, K., Xolile Fuku, Gene T. Mola, E. Manikandan, J. Kennedy, and M. Maaza. Photoluminescence of well-aligned ZnO doped CeO₂ nanoplatelets by a solvothermal route. *Materials Letters*, 183(2016), 351-354.
- [44] Saravanan, T., & Saritha, G. (2013). Buck converter with a variable number of predictive current distributing method. *Indian Journal of Science and Technology*, 6(5S), 4583-4588.
- [45] Parthasarathy, R., Ilavarasan, R., & Karrunakaran, C. M. (2009). Antidiabetic activity of Thespesia Populnea bark and leaf extract against streptozotocin induced diabetic rats. *International Journal of PharmTech Research*, 1(4), 1069-1072.
- [46] Hanirex, D. K., & Kaliyamurthi, K. P. (2013). Multi-classification approach for detecting thyroid attacks. *International Journal of Pharma and Bio Sciences*, 4(3), B1246-B1251
- [47] Kandasamy, A., Mohan, R., Lydia Caroline, M., & Vasudevan, S. (2008). Nucleation kinetics, growth, solubility and dielectric studies of L-proline cadmium chloride monohydrate semi organic nonlinear optical single crystal. *Crystal Research and Technology: Journal of Experimental and Industrial Crystallography*, 43(2), 186-192.
- [48] Srinivasan, V., Saravanan, T., Udayakumar, R., & Saritha, G. (2013). Specific absorption rate in the cell phone user's head. *Middle-East Journal of Scientific Research*, 16(12), 1748-50.
- [49] Udayakumar R., Khanaa V., & Saravanan T. (2013). Chromatic dispersion compensation in optical fiber communication system and its simulation, *Indian Journal of Science and Technology*, 6(6), 4762-4766.
- [50] Vijayaragavan, S.P., Karthik, B., Kiran, T.V.U., & Sundar Raj, M. (1990). Robotic surveillance for patient care in hospitals. *Middle-East Journal of Scientific Research*, 16(12), 1820-1824.